

Technical Data

TOTAL SERVICE SERIES

PX DETROIT DIESEL 40

Product Description

PX Detroit Diesel 40 is a monograde SAE 40 and falls into the category of a superior performance "Series 2" diesel engine oil.

Applications/ Benefits

PX Detroit Diesel 40 is a very low ash lubricant to ensure minimal crown land piston deposits and to prevent top ring carbon build up. Specifically, this product has been formulated to take account of the need for oil which will provide excellent valve train wear protection and at the same time combat the likelihood of engine cylinders becoming "Glazed" under less severe operating conditions.

- Helps extend engine life.
- Minimizes piston and combustion chamber deposits.
- Contains anti-corrosion agents.
- Recommended for Detroit Diesel 2 - Cycle engines, including marine models.

Typical Characteristics

Test Description	Method	Result
SAE Viscosity Grade	SAE J300	40
Specific Gravity @ 15 0 C	ASTM D-4052	0.891
Kinematics Viscosity		
@ 40C (cSt)	ASTM D-445	136
@ 100 0 C (cSt)	ASTM D-445	14.4
Viscosity Index	ASTM D-2270	104
Sulphated Ash %	ASTM D-874	0.85

Specifications

- API: CF2/ SG
- ACEA E2
- MACK EO/ K2

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au