

# Technical Data

## TOTAL SERVICE SERIES

## PX HYDRAULIC OIL 22

### Product Description

PX Hydraulic Oil 22 is a premium zinc-based anti-wear hydraulic oil, made from premium base oils fortified with rust, oxidation and foam inhibitors. Using this product will promote excellent cleanliness, longer fluid life, demulsibility and filterability even when severely contaminated with water.

### Applications/ Benefits

PX Hydraulic Oil 22 is for use in hydraulic systems requiring anti-wear oils, particularly systems with vane pumps operating at pump pressures above 7MPa (1000 psi) and speeds above 1200 rpm. It is also suitable for use in other systems where wear rates are high while using conventional oils.

PX Hydraulic Oil 22 has a long change life due to the superior oxidative and thermal stability additive system and rust protection. The excellent air release properties minimise compressibility and prevent noisy and erratic operation.

PX Hydraulic Oil 22 is compatible with hydraulic oils that contain a non-zinc based anti-wear system.

### Typical Characteristics

Test Description	Result
Specific Gravity @ 15 0 C	0.867
Flash Point, Deg. C	>210
Pour Point, Deg. C	-20
@ 40C (cSt)	21
@ 100 0 C (cSt)	4.3
Viscosity Index	102
Foam, ASTM D-892	50/0

### Specifications

ISO 22	DIN 51524 Part 2	Denison HF-1, HF-2, HF-0
Lee-Norse 100-1	Ford M-6C32	US Steel 136, 127
Cincinnati Milacron P-68, P-69, P70	Jeffery No. 87	B F Goodrich 0152
Racine, variable volume vane pumps	General Motors LH-04-1, LH-06-1, LH-15-1	
Vickers V-104C & 35VQ25 vane, 1-286-S, M2950-S	Commercial Hydraulics (except PM500 )	AFNOR E48-603

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS  
2 Paul Court Dandenong Victoria 3175  
Tel. +61 3 9791 7661

[www.phoenixlubricants.com.au](http://www.phoenixlubricants.com.au)  
Email: [info@phoenixlubricants.com.au](mailto:info@phoenixlubricants.com.au)