SAFETY DATA SHEET

Issue Date: Version 1.0 16/10/2017



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

PX PETROL INJECTOR CLEANER

Code : PETROLINJECTOR

Use: Injector cleaner additive for petrol fuelled vehicles.

Name: Phoenix Lubricants Pty Ltd (ABN 41 820 770 617)

Address: 2 Paul Court, Dandenong Vic 3175

Telephone : (03) 9791 7661 **Facsimile** : (03) 9791 8831

Email : info@phoenixlubricants.com.auWeb : www.phoenixlubricants.com.au

2. HAZARD IDENTIFICATION

CLASSIFIED AS A HAZARDOUS CHEMICAL ACCORDING TO THE CRITERIA OF SAFE WORK AUSTRALIA

Hazard Class and Category:

Flammable Liquids Category 4
Skin Corrosion/Irritation Category 2
Carcinogen Category 2
Specific Target Organ Toxicity (Single Exposure) Category 3
Aspiration Hazard Category 1

Signal Word: DANGER

GHS Pictograms:





Hazard Statements:

H227: Combustible liquid H315: Causes skin irritation

H351: Suspected of causing cancer H335: May cause drowsiness or dizziness

H304: May be fatal if swallowed and enters airways

Precautionary Statements:

P301+P310+P331 IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do not induce vomiting.

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P303+P361+P352: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash skin with plenty of soap and water.

P261: Avoid breathing mist, vapours or spray.

P271: Use only outdoors or in a well-ventilated area.

P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTER or doctor/ physician if you feel unwell.

2. HAZARD IDENTIFICATION CONT.

Print Date: 17/10/2017 Page 1 of 7 SDS-Petrol Injector Cleaner

P403+P235: Store in a well ventilated place. Keep cool.

P210: Keep away from flames and hot surfaces. No smoking.

P280: Wear protective gloves, clothing and eye protection.

P264: Wash hands thoroughly after handling.

P370+378: In case of fire: Use sand, earth, or chemical foam to extinguish.

P405: Store locked up.

P501: Dispose of contents and container as hazardous waste.

Poison Schedule : S5

3. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS:

Component	CAS No.	Conc, %
Distillates, Petroleum straight run middle	64742-46-7	60-85%
(highly refined mineral oil)		
Phenol, (dimethylamino)methyl-,	No CAS, EC 937-027-0	2-20%
polyisobutylene derivatives		
Poly[oxy(1,2-propanediyl)], .alpha(3-	Proprietary	1-20%
aminopropyl).omegahydroxy-,		
C12-15 alkyl ethers		

4. FIRST AID MEASURES

REMOVE FROM EXPOSURE IF SAFE TO DO SO

Swallowed: • Do not induce vomiting

Unlikely exposure route • Keep at rest.

• Seek immediate medical attention

Eye : • Hold eye open

• Irrigate with water until irritation subsides (at least 15 minutes)

Seek immediate medical attention

Skin: • Flush area with large amounts of water

Wash skin with soap and water

• Remove contaminated clothing, and wash before reuse

· Seek medical attention if skin irritation occurs

Inhalation: • Remove from exposure if safe to enter area

· Loosen/remove clothing

• Move to fresh air

Administer artificial respiration if breathing has stopped

• Seek immediate medical attention

ADVICE TO DOCTOR

- Avoid gastric lavage: risk of aspiration of product to the lungs with potential to cause chemical pneumonitis.
- Treat according to symptoms

AUSTRALIAN POISONS INFORMATION CENTRE 24 HOUR SERVICE 13 11 26

NEW ZEALAND POISONS INFORMATION CENTRE 24 HOUR SERVICE 0800 764 766

5. FIRE FIGHTING MEASURES

Flash point : >60°C

Fire & Explosive Properties : Combustible Liquid. May ignite when heated or in

contact with hot surfaces. Spray mist may ignite.

Suitable Extinguishing

Media

Suitable extinguishing media are dry chemical

or foam.

Hazards from Combustion :

Products

Product is a mobile liquid. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low lying spaces. Fire decomposition products from this product may be toxic if inhaled. (Carbon dioxide and carbon

monoxide, smoke and soot)

Precautions for Fire : Fighters - Special Equipment Positive pressure self-contained breathing apparatus (SCBA) and protective suit

· Protective fire fighting clothing

6. ACCIDENTAL RELEASE MEASURES

Spills or Leaks

Restrict access to area until clean-up is completed Wear PPE as per this SDS

Absorb / contain waste, use earth, vermiculite, inert

material

If there is a build up of vapours or mist in the clean up area, we recommend the use of a respirator.

Collect and seal in appropriate container

Label the container

Create bund

Do not contaminate surface waters - depletion of

oxygen in the water will occur.

Observe regulatory reporting requirements (Incident Notification)

Protect drains from potential spills to minimise contamination. In the case of large

spills contact the appropriate authorities.

Disposal :

 Dispose of in accordance with State, Local Government, EPA or related Regulations or Codes of Practice.

7. HANDLING AND STORAGE

Precautions for Safe : Handling

- Eye wash and safety shower to be available in the workplace.
- Wear PPE as per this SDS
- Compliant eyewash to be provided for external work.
- Observe good personal hygiene practices.
- · Wash hands thoroughly after handling.
- Avoid contact with skin and eyes.
- Use only in well ventilated areas.
- Wear respiratory protection if vapours present.
- Product is readily combustible, avoid sources of heat or ignition when handling
- No eating or drinking in the work area.
- Use grounding leads to avoid discharge (electrical spark)

Conditions for Safe :

Storage

- Store away from food, drink and animal feedstuffs.
- Combustible Liquid Store away from oxidising agents.
- Provide ventilation and containment of spills.
- Separate or segregate from incompatibles (in accordance with regulatory requirements).
- · Avoid direct sunlight.
- Keep protected from weather.
- · Provide spill kit.

LEGEND			
DRY AGENT Do not use water			
ALCOHOL RESISTANT FOAM •2 OR •3			
When • appears in front of 2 or 3 in Hazchem code use alcohol resistant foam if available			
V			
Substances can be violently or even explosively reactive, including combustion			
LTS Liquid-Tight Chemical Protective Suit with BA. Full FIRE KIT to also be worn for protection when:			
Liquid Oxygen Liquefied Toxic Gas (Division 2.3) Toxic Gas with sub-risk 2.1 or 5.1			
Class or sub-risk 3 Division 5.1 PGI with sub-risk 6.1 or 8 transported at temperature >100°C are involved			
DILUTE			
May be washed to drains with large quantities of water, consider EPA or Water Authority			
CONTAIN Prevent, by any means available, spillage from entering drains or water courses			
F			
People to be warned to stay indoors with all doors and windows closed. Evacuation may need to be considered.			
Joint Incident Control decision			

7. HANDLING AND STORAGE CONT.

Container Type

• Store in original packaging as approved by manufacturer or regulatory direction. Do not pressurise, cut, heat or weld containers- residual vapours are flammable.

Incompatible Materials

• Natural Rubber, Butyl Rubber, EPDM, Polystyrene

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CONSTITUENT DATA

Components	CAS-No.	Туре	Value
Petroleum distillates, Oil Mist	64741-44-2	TWA	5 mg/m³

ENGINEERING CONTROLS

 Provide local exhaust when comfort levels might be exceeded, or where spray mists occur. Use explosion-proof ventilation equipment

PERSONAL PROTECTION

Eye Protection : Wear safety glasses with side shields in accordance with AS/NZS1337, Eye

protection for industrial applications.

Gloves : Wear chemical protective gloves (eg nitrile/PVC) in accordance with AS/NZS 2161.1 -

Occupational protective gloves, selection, use and maintenance where contact

may occur.

Clothing: Wear body protective clothing and industrial footwear in accordance with AS2919 -

Industrial clothing.

Respiration: If ventilation is inadequate, wear an approved organic vapour/particulate respirator in

accordance with AS/NZS1715 - Selection, use and maintenance of respiratory

protective devices



















Available

Side shields

Nitrile/PVC

Industial

Non slip

Organic Vapour/particulate

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear, pale yellow liquid
Odour : Mild hydrocarbon odour

pH (33% sol'n) : Not Applicable Vapour Pressure (kpa) : 0.1 kPa at 20°C

> Vapour Density : >5x air Boiling Point : 170 – 360 °C

Freezing / Melting Point : No specific data. Liquid at normal temperatures

Solubility in Water : Negligible

Specific Gravity: 0.835-0.855 at 20 °C.

INFORMATION FOR FLAMMABLE MATERIALS

Flash Point >60°C
Percent Volatiles : 90
Upper Explosive Limit : 1%
Lower Explosive Limit : 6%
Auto ignition Temperature : >220 °C.

ADDITIONAL INFORMATION

Specific Heat Value : N/A
Particle Size : N/A

Print Date: 17/10/2017 Page 4 of 7 SDS-Petrol Injector Cleaner

9. PHYSICAL AND CHEMICAL PROPERTIES CONT.

VOC Content : 90% Evaporation Point : N/A

Kinematic Viscosity @ 40°C : 1.5-6 mm²/s

Kinematic Viscosity@ 100°C : N/A Octanol / Water Partition : N/A

Coefficient

Saturation Vapour : N/A

Concentration

Decomposition: N/A

Temperature

10. STABILITY AND REACTIVITY

Chemical Stability: This product should be kept in a cool place, preferably below 50 deg. C. Keep

containers tightly closed.

Incompatible Materials: Strong oxidising agents. May attack natural rubber, butyl rubber, and polystyrene.

Hazardous Decomposition : Combustion forms carbon dioxide, and if incomplete, carbon monoxide and smoke.

Products

11. TOXICOLOGICAL INFORMATION

ACUTE HEALTH EFFECTS (IMMEDIATE OR WITHIN 14 DAYS - SHORT TERM)

Swallowed (Oral) : Small amounts of liquid aspirated into the lungs during ingestion, or from vomiting,

may cause chemical pneumonitis, or pulmonary oedema. This may be fatal. Symptoms may be delayed – in all suspected cases seek medical attention. Swallowing any amount of this product will result in headaches, nausea, dizziness,

and tracheal burning.

Eye : This product is a mild eye irritant. Symptoms may include stinging and reddening of

eyes and watering which may become copious. This product will not permanently

damage the eye tissue.

Skin (Dermal): This product may be irritating to the skin with prolonged exposure. It may result in

dryness and cracking.

Inhalation: Exposure to large concentrations of vapour over an extended period of time may

result in muscle weakness, tingling in hands and feet, blurred vision, headaches,

nausea, loss of appetite, hallucinations, and possible loss of consciousness.

CHRONIC (MEDIUM OR LONG TERM)

No data available

CARCINOGENICITY

• An ingredient may possibly cause cancer in humans, based on animal studies.

12. ECOLOGICAL INFORMATION

Ecotoxicity: Toxic to aquatic life.

Persistence / Degradability : Degrades by photooxidation in air. May persist in anaerobic conditions

Mobility Components will bioaccumulate. Most will partition slowly to air. If product enters soil,

it will be highly mobile and may contaminate ground water.

Environmental Fate

(Exposure) Do not allow waste product to reach waterways, drains and sewers

Print Date: 17/10/2017 Page 5 of 7 SDS-Petrol Injector Cleaner

13. **DISPOSAL CONSIDERATIONS**

Disposal Methods Special Precautions for Landfill or Incineration

This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration in the appropriate equipment. Packaging may still contain fumes and vapours that may ignite if heated and harmful.

Ensure that empty packaging is allowed to dry. This product is NOT suitable for disposal by either landfill or via municipal sewers,

drains, natural streams or rivers.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS DANGEROUS GOODS DUE TO HIGH FLASHPOINT

UN Number None **UN Proper Shipping Name** None

Dangerous Goods Class

None

and Subsidiary Risk

None

Packing Group : Hazchem Code : None **Dangerous Goods Segregation:**

This product is classed as a Combustible liquid. It must be segregated from Class 5 (oxidising) products in placard loads. Please consult the Australian Dangerous Goods Code for Transport by Road and Rail for information.

15. **REGULATORY INFORMATION (AUSTRALIA)**

COUNTRY: Australia **INVENTORY: AICS STATUS:** Listed

POISON SCHEDULE: S5 Liquid hydrocarbons

Hazardous Chemical according to the criteria of Safe Work Australia.

16. OTHER INFORMATION

References: For detailed advice on personal protective equipment, refer to the following Australian Standards:

> • HB9 (Handbook 9) Manual of industrial personal protection • AS/NZS 1337: Eye protectors for industrial applications

• AS/NZS 1715: Selection, use and maintenance of respiratory devices

• AS/NZS 1716: Respiratory protective devices • Ingredient Material Safety Data Sheets

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AICS Australian Inventory of Chemical Substances **SWA** Safe Work Australia, formerly ASCC and NOHSC Chemical Abstracts Service Registry Number **CAS** number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

N/A Not Available

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

CONTACT POINT

Phoenix Lubricants Pty Ltd, 2 Paul Court, Dandenong Vic, (03) 9791 7661

All reasonable care has been taken to ensure that the information and advice contained herein is accurate at the time of printing. However, Phoenix Lubricants Pty Ltd accepts no tortious or contractual liability for any loss or damages suffered as a consequence of reliance on the information and advice contained herein.

Note:

This SDS is derived from International and Australian data and is formatted generally in accordance with the Safe Work Australia Code of Practice. Modifications are not made to technical data except where terminology is unclear or additional information is required to satisfy Australian requirements.

SDS Issue Date : 16/10/2017

Supplier : Phoenix Lubricants Pty Ltd