

Technical Data

TOTAL SERVICE SERIES

PX SUPER OUTBOARD TC-W3

Product Description

PX Super Outboard TC-W3 meets the requirement of National Marine Manufacturer's Association (NMMA) TC-W3 specification. It contains premium quality lubricating base stocks plus ashless additives and increased detergency to give superior protection in all types of high performance water cooled two-cycle engines calling for TC-W3.

Applications/ Benefits

PX Super Outboard TC-W3 is self-mixing and can be used premixed or for oil injection systems. This product is recommended for use in all outboard marine engines including Evinrude, Chrysler, Force, Johnson, Mariner, Mercury, Suzuki and Yamaha where TC-W3 is called for.

- Protects engine against failures due to scuffing, ring sticking, port deposits, bearing failures and plug fouling
- Mixes easily with fuel for pre-mix applications
- Excellent rust protection

Typical Characteristics

| Test Description | Result |
|---------------------------|--------|
| Specific Gravity @ 15 0 C | 0.872 |
| Flash Point, Deg. C | 93 |
| Pour Point, Deg. C | <-21 |
| Kinematics Viscosity | |
| @ 40C (cSt) | 42.4 |
| @ 100 0 C (cSt) | 7.1 |
| Viscosity Index | 128 |

Specifications

- NMMA: TC-W3

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au