

Technical Data

TECHNICIAN SERIES

PX M2 5W-30

Product Description

PX M2 5W-30 is a fully synthetic engine oil that has been specifically designed for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA A5/B5, API SN/CF, ILSAC GF-4 or earlier specification 5W-30 lubricant. It has been developed using the latest in lubricating oil technology ensuring premium engine protection and optimum fuel efficiency.

PX M2 5W-30 is recommended in Ford vehicles that require a 5W-30 lubricant that meets Ford specification WSS-M2C913-A, B, C or D.

Applications/ Benefits

- Excellent low temperature viscosity promotes quick start-up full lubrication
- Emission system durability & increased fuel economy
- Turbocharger/ supercharger protection
- Piston cleanliness and engine sludge protection
- Wear protection and extended service life
- Meets all engine test performance requirements of API SN but exceeds the Phosphorus level for that classification.

Typical Characteristics

Test Description	Result
SAE Viscosity Grade	5W-30
Specific Gravity @ 15 0 C	N/A
Kinematics Viscosity	
@ 40C (cSt)	60
@ 100 0 C (cSt)	10.7
Viscosity Index	171
TBN (mgKOH/g)	12.1

Specifications

- API: SN/CF
- Ford: WSS-M2C913-D
- Jaguar Land Rover: STJLR03.5003
- ACEA: A5/B5
- Renault: RN 0700

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au