

Technical Data

TECHNICIAN SERIES

PX SYNCRO SHIFT 75W

Product Description

PX SYNCRO SHIFT 75W is a fully synthetic PAO high tech gear oil formulated with advanced additive technology providing the best available protection for modern gearboxes, transfer & drive cases, especially in arduous conditions.

Applications/ Benefits

PX SYNCRO SHIFT 75W is ideal for use in most manual transmissions where an automatic transmission fluid is recommended. Its superior low viscosity PAO formulation not only provides excellent shift performance at low temperatures but provides maximum protection to all integral components.

- Especially recommended for synchronised manual transmissions.
- Optimized for use with Brass, Bronze, Paper, Carbon & Molybdenum synchronisers
- Extends synchroniser life
- Improves Shift
- Ideal for use in Gearboxes, Transfer & Drive casings that require Automatic Transmission Fluid (ATF)
- Offers extreme thermal stability with exceptional cleanliness

Typical Characteristics

SAE Viscosity Grade	75W
Specific Gravity @ 15 deg. C	0.846
Flash Point	225
@ 40C (cSt)	31.9
@ 100 0 C (cSt)	6.3
Viscosity Index	155
Brookfield @ -40 deg. C. (m.Pa.s)	7600
Pour Point	-51

Specifications/ Suitable for use

- API: GL4 / GL4 Plus
- BOT: 338
- FORD: M2C-200-D2
- VW: TL 52171 (G 052 171 A2)
- SAE: 75W
- BOT 350M3
- Tremec (T-56)
- VW: TL 52512 (G 052 512 A2)

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX[®]

PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au