

# Technical Data

## TECHNICIAN SERIES

### PX TRANSMATIC CVT 3

#### Product Description

PX Transmatic CVT 3 is a synthetic next generation CVTF (Continuously Variable Transmission Fluid). It is blended with high-performance synthetic base oils and additives for lubrication which guarantees excellent operation of the gearbox. It has proof of performance supported by Bosch Belt Box Long Durability Cycle Test, FZG Scuffing wear test and Anti-Shudder Durability (JASO: LVFA M349).

#### Applications/ Benefits

PX Transmatic CVT 3 provides the appropriate viscosity, performance and metal on metal friction between belt and pulley within the transmission system. It also provides severe metal anti-wear and anti-foaming performance that is required by continuously variable transmissions.

- Provides excellent friction, oxidation and thermal stability
- Outstanding anti-wear properties and oil film thickness
- Longer life due to fully synthetic base and carefully selected additives
- Excellent shear stability for consistent shift

#### Typical Characteristics

Test Description	Result
Colour	Green
Specific Gravity @ 15 0 C	0.852
Flash Point, Deg. C	198
Pour Point, Deg. C	-45
Viscosity Index	200
@ 40C (cSt)	33.1
@ 100 0 C (cSt)	6.14

#### Specifications

- Toyota FE
- Nissan NS-3
- Honda HCF-2
- Mitsubishi Dia Queen CVTF-J4
- Daihatsu Amix CVTF-DFE
- Suzuki CVTF Green 2

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS  
2 Paul Court Dandenong Victoria 3175  
Tel. +61 3 9791 7661

[www.phoenixlubricants.com.au](http://www.phoenixlubricants.com.au)  
Email: [info@phoenixlubricants.com.au](mailto:info@phoenixlubricants.com.au)