

# Technical Data

## TECHNICIAN SERIES

### PX SYNCRO SHIFT 75W-80

#### Product Description

PX SYNCRO SHIFT 75W-80 is a fully synthetic gear oil formulated with advanced additive technology providing the best available protection for synchronized/ automated manual transmissions. It can also be used in a range of existing and new vehicles using ZF transmissions, including those fitted with ZF-intarders.

#### Applications/ Benefits

The additive used in PX SYNCRO SHIFT 75W-80 has over 20 million kilometres of field testing in commercial vehicles and is an OEM endorsed additive technology.

This technology delivers the high expectation of ease of gear shifting, extended oil drain interval and thermal durability.

- Reduces operating temperatures.
- Recommended for synchronised manual transmissions.
- Recommended for automated manual transmissions.
- OEM endorsed additive technology.
- Drain intervals up to 320,000 km.

#### Typical Characteristics

SAE Viscosity Grade	75W-80
Specific Gravity @ 15 deg. C	0.857
Flash Point	240
@ 40C (cSt)	62
@ 100 0 C (cSt)	10.3
Viscosity Index	154
Pour Point	- 50 °C

#### Specifications

- API: GL4
- DAF
- MAN: 341 Type Z4/ E3
- MB: 235.4
- RENAULT
- SAE: 75W-80
- EATON
- IVECO
- VOLVO: 97307
- ZF: TE-ML 01L, 02L, 08, 13, 16K

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS  
2 Paul Court Dandenong Victoria 3175  
Tel. +61 3 9791 7661

[www.phoenixlubricants.com.au](http://www.phoenixlubricants.com.au)  
Email: [info@phoenixlubricants.com.au](mailto:info@phoenixlubricants.com.au)