

# Technical Data

## TOTAL SERVICE SERIES

### PX 4T RED 30

#### Product Description

PX 4T RED 30 has been specially formulated to lubricate 4-Stroke petrol and naturally aspirated diesel engines like those found in ride-on and push type mowers.

#### Applications/ Benefits

With its modern anti-wear package and low combustion ash forming properties, PX 4T RED 30 ensures engine cleanliness and wear is effectively maintained.

- Helps extend engine life.
- Ensures engine cleanliness.
- Suits petrol or diesel engines.
- Recommended for Briggs & Stratton.

#### Typical Characteristics

Test Description	Method	Result
SAE Viscosity Grade	SAE J300	30
Specific Gravity @ 15 0 C	ASTM D-4052	0.89
Kinematics Viscosity		
@ 40C (cSt)	ASTM D-445	102
@ 100 0 C (cSt)	ASTM D-445	11.5
Viscosity Index	ASTM D-2270	100

#### Specifications

- API: SG/ CD
- SAE: 30

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS  
2 Paul Court Dandenong Victoria 3175  
Tel. +61 3 9791 7661

[www.phoenixlubricants.com.au](http://www.phoenixlubricants.com.au)  
Email: [info@phoenixlubricants.com.au](mailto:info@phoenixlubricants.com.au)