

# Technical Data

## TOTAL SERVICE SERIES

## PX BRAKE FLUID DOT 3 CLEAR

### Product Description

PX Brake Fluid DOT 3 Clear is a high boiling polyglycol-based fluid for universal use in modern brake and clutch systems. It contains corrosion and oxidation inhibitors that protect rubber and metallic components present in the vehicle's brake system. It meets and exceeds all the DOT 3 requirements for motor vehicle brake fluids.

PX Brake Fluid DOT 3 Clear 3 brake fluids are recommended for passenger vehicles, motorcycles, light and heavy duty vehicles and equipment where it is required a non-petroleum based DOT 3.

### Applications/ Benefits

- Superior resistance against water absorption/ retainment
- High Boiling Point to guard against vapour lock brake failure
- High corrosion resistance
- Suitable for disc or drum brakes

### Typical Characteristics

Test Description	Result
Appearance	Clear amber
Density at 20°C	1040 kg/m <sup>3</sup>
Kinematic Viscosity at 40°C	7.9 mm <sup>2</sup> /s
Flash Point	130°C/266°F
Ignition Temperature	>200°C/>392°F
Boiling Point	≥205 °C
Wet Boiling Point	≥140 °C
pH Value	8.8

### Specifications

- AS 1960-2005 Grade 1
- FMVSS No. 116 DOT 3
- ISO 4925 Class 3
- SAE J1703

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS  
2 Paul Court Dandenong Victoria 3175  
Tel. +61 3 9791 7661

[www.phoenixlubricants.com.au](http://www.phoenixlubricants.com.au)  
Email: [info@phoenixlubricants.com.au](mailto:info@phoenixlubricants.com.au)