

Technical Data

TOTAL SERVICE SERIES

PX HD COOLANT LLY

Product Description

PX HD COOLANT LLY is a Long Life Coolant Concentrate with advanced OAT (Organic Acid Technology) corrosion inhibitors in Ehtylene Glycol. It is free of Silicate, Phosphate, Amine, Borate and Nitrite. PX HD COOLANT LLY is designed to provide superior corrosion protection and anti-freeze/anti-boil protection for all types of petrol, diesel and gas engines in light commercial and passenger vehicles, heavy duty commercial, industrial, on highway, marine, mining and stationary applications.

Applications/ Benefits

When diluted 50% water, PX HD COOLANT LLY provides;

- When diluted with 50% water
- Extended Service life:
- Passenger vehicles and light commercial transporters – 400,000km/6 years (whichever comes first).
- Heavy duty vehicles – 400,000km/6 years,/12,000 hrs.
- Excellent anti-freeze/anti-boil protection against metals corrosion, cavitation and liner pitting.
- Minimal disposal volume of spent coolant required.
- Optimal reliability and operating life of water pump (silicate free product).
- Maximisation of fuel economy by keeping the engine at the optimal operating temperature.
- Protection against scale, rust and residue build-up.
- Formulation tested and manufactured according to Australian conditions AS 2108 - 2004 (Type A) that exceeds ASTM

Principle Uses

All on-road and stationary petrol, diesel and gas fuelled engines, including passenger and light commercial vehicles, buses, tractors, trucks, also marine engines, mining equipment and stationary engines.



PHOENIX®

PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au

Specifications

- AS/NZS 2108.1:1997 (Australian Standard) Type A
- ASTM D3306 (and D4656)
- ASTM D4985 (and D5345)
- ASTM D6210 VOLVO
- Audi/SEAT/Skoda
- BMW N600 69.0
- BR 637
- BS 6580 (British Standard)
- BT-PS-606A (MIL-Belgium)
- Caterpillar EC-1
- Cummins 90 T8-4
- DAF-Leyland 74001
- Daihatsu
- DCEA 615 (MIL-France)
- Detroit Diesel/Perkins
- E/L-1415b (MIL-Italy)
- Ford WSS-M97B44-D
- FSD 8704 (MIL-Sweden)
- FVV Heft R443 (Germany)
- General Motors GM 1899M
- General Motors GM 6277M
- Honda
- Hyundai
- ISUZU
- JASO M325 (Japan) LLC
- JIS K2234 (Japan) LLC
- Komatsu
- Mack-RVI
- MAN 324 (Diesel Engines)
- Mazda MES 121C
- Mercedes-Benz Sheet 325.3
- Mitsubishi ES-X64216
- NATO S-757
- Navistar
- SAAB
- SAE J1034
- Scania (Tech Info. TI 02-98)
- Subaru
- Toyota TS K2601 G
- UNE 26-361-88/1
- Volkswagen VW TL774D

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au