

Technical Data

TOTAL SERVICE SERIES

PX PROTECTOR PLUS

Product Description

PX PROTECTOR PLUS Concentrate is a glycol based product containing organic inhibitors to protect cooling systems from corrosion and scale formation. The product when mixed with water is green and self-indicating.

Applications/ Benefits

- Provides protection for passenger and light commercial vehicles for 100,000kms / 3 years (whichever comes first.)
- Provides lubrication to water pumps to minimize seal problems.
- Excellent protection of all metals commonly found in the engine cooling system.
- Maximises fuel economy by keeping the engine at the optimum operating temperature.
- Protects against scale, rust and residue build up.
- Formulated tested and manufactured in Australia for Australian conditions.
- Exceeds the following performance and specification requirements:-
- ASTM's D1384, D4340, D2809, D2570, D1881, D1287, D1121, D3634
- AS2108 - 2004 (Type B) and most international performance specifications.

Instructions for Use

Before treatment, pre-clean the cooling system by: -

Draining the existing coolant/ inhibitor and clean the system to remove any rust, dirt, oil and built up residue.

Use Radiator Flush to clean the system effectively and thoroughly.

Initial Dosage:

500ml to every 8 litres of clean, soft water.

Preventative Maintenance:

Never top up with water as this will dilute the inhibitor. Always top up with PX PROTECTOR PLUS mixed with clean, soft water. Phoenix recommends that this product does not get mixed with other brands of coolants/ inhibitors.

Passenger Vehicles:

PX PROTECTOR PLUS should be drained and replaced every 100,000 kms or 3 years, whichever comes first.

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au