

Technical Data

TOTAL SERVICE SERIES

PX METH-X 50 25W-50

Product Description

PX Meth-X 50 is a high quality mineral based engine oil designed specifically for big bore naturally aspirated, turbocharged or supercharged engines. PX Meth-X 50 can also be used in passenger cars, light commercials and motorcycles where API SL/ CI-4 and SAE 25W-50 are called for.

Applications/ Benefits

PX Meth-X 50 is particularly suitable for vehicles using harsh fuels e.g. methanol. Designed with motorsport in mind, Meth-X 50 is the perfect choice for competition use whether it's a club speed event, speedway, rally or circuit/ drag racing.

- Racing engines
- Big bore street machines
- Engines running on methanol
- Inboard power / ski boats
- Veteran 4-Stroke air/ water cooled motorcycles
- Engines running flat tappet cams
- Non friction modified

Typical Characteristics

Test Description	Method	Result
SAE Viscosity Grade	SAE J300	25W-50
Specific Gravity @ 15 0 C	ASTM D-4052	0.889
@ 40C (cSt)	ASTM D-445	225
@ 100 0 C (cSt)	ASTM D-445	20
CCS @ -10 Deg. C. (cP)		9212
HTHS (cP)		5.41
Total Base Number		11.2
Zinc ppm		1206
Viscosity Index	ASTM D-2270	115

Specifications

API: SL/ CI-4

JASO: MA

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au