

Technical Data

TOTAL SERVICE SERIES

PX MONO 40

Product Description

PX Mono 40 has been formulated to lubricate turbo-charged and normally aspirated diesel's operating under severe stress conditions in both on and off highway situations.

Applications/ Benefits

With its low phosphorous level and low sulphated ash content ensures its use for mixed fleet operators including those with petrol engines with catalytic converters. PX Mono 40 meets or exceeds the requirements of CF-4/SG engine oil. It provides a high level of protection against wear, sludge formation and acid corrosion. PX Mono 40 assists in maintaining engine cleanliness and extending the life of all moving parts subject to wear.

- Helps extend engine life.
- Minimizes piston and combustion chamber deposits.
- Contains anti-corrosion agents.
- Recommended for petrol or diesel engines.

Typical Characteristics

Test Description	Method	Result
SAE Viscosity Grade	SAE J300	40
Specific Gravity @ 15 0 C	ASTM D-4052	0.892
Kinematics Viscosity		
@ 40C (cSt)	ASTM D-445	140
@ 100 0 C (cSt)	ASTM D-445	14.7
Viscosity Index	ASTM D-2270	99

Specifications

- API: CF-4/ SG
- CCMC G4, D4, PD-2

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au