

SAFETY DATA SHEET



PHOENIX®

Issue Date: March 2013

Revision 2.2 Date: 12/08/2019

1. IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

PX SEMI FLUID GREASE EP 00

Code : GRSFL00
Use : Multipurpose Extreme Pressure Grease
Name : Phoenix Lubricants Pty Ltd (ABN 41 820 770 617)
Address : 2 Paul Court, Dandenong Vic 3175
Telephone : (03) 9791 7661
Facsimile : (03) 9791 8831
Email : info@phoenixlubricants.com.au
Web : www.phoenixlubricants.com.au

2. HAZARD IDENTIFICATION

**NOT A HAZARDOUS CHEMICAL ACCORDING TO CRITERIA OF SAFE WORK AUSTRALIA
NOT DANGEROUS GOODS FOR TRANSPORT ACCORDING TO AUSTRALIAN DANGEROUS GOODS CODE (ADGC)**

Poisons Schedule : Not Scheduled

3. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS:

Component	CAS No.	% Proportion
Heavy, Solvent Refined Paraffinic Mineral Oil	64742-54-7 64742-52-5	80 - 85%
Lithium Complex Soap	4485-12-5	<20%
Sulphur/Zinc EP Agents and Antioxidants, Nonhazardous	68649-42-3	1.5%

The petroleum oils in this product contain less than 3% DMSO extract as measured by IP346 test method.

4. FIRST AID MEASURES

REMOVE FROM EXPOSURE IF SAFE TO DO SO

- Swallowed** : *Unlikely exposure route*
- Ingestion of small quantities should not cause irritation.
 - Wash mouth with water
 - Give a glass of water to drink
 - Do not induce vomiting
 - Seek immediate medical attention
- Eye** :
- Remove contact lenses if present and easy to do so
 - Hold eye open
 - Wash gently for fifteen (15) minutes
 - Seek medical attention
- Skin** :
- Flush skin with water for fifteen (15) minutes or
 - Wash skin with soap and water
 - Remove contaminated clothing
 - If irritation symptoms develop seek medical attention
- Inhalation** : *Unlikely exposure route*
- Remove from exposure to open space or fresh air
 - Not expected to lead to irritation

4. FIRST AID MEASURES CONT.

ADVICE TO DOCTOR : • Treat symptomatically with supportive care.
• For further information contact:

AUSTRALIAN POISONS INFORMATION CENTRE
24 HOUR SERVICE 13 11 26

NEW ZEALAND POISONS INFORMATION CENTRE
24 HOUR SERVICE 0800 764 766

5. FIREFIGHTING MEASURES

Hazchem Code : 3Y

Fire & Explosive Properties : C2 Combustible liquid - Flashpoint >250°C

Suitable Extinguishing Media : In case of fire, appropriate extinguishing media includes:

- Dry Chemical Powder
- CO₂
- Foam

Do not use water jets. Use water spray to cool fire exposed containers.

Hazards from Combustion Products : Combustion produces oxides of carbon, nitrogen and sulphur. May react with strong oxidising agents.

Precautions for Fire Fighters - Special Equipment : • Positive pressure self-contained breathing apparatus (SCBA)
• Protective fire fighting clothing
• Fight from upwind

6. ACCIDENTAL RELEASE MEASURES

Spills or Leaks : • Wear PPE as per this SDS
• Remove ignition sources
• Absorb / contain waste, use earth, vermiculite, inert material
• Collect and seal in appropriate container
• Label the container
• Cover all drains
• Use spark proof tools
• Surfaces will be slippery
• Create bund
• Observe regulatory reporting requirements (Incident Notification)

Disposal : • Dispose of in accordance with State, Local Government, EPA or related Regulations or Codes of Practice.

HAZCHEM Emergency Action Code			
FOR FIRE OR SPILLAGE			
1	COARSE SPRAY		
2	FINE SPRAY		
3	FOAM NORMAL PROTEIN		
4	DRY AGENT		
*	ALCOHOL RESISTANT		
P	V	LTS	DILUTE
R			
S	V	BA & FIRE KIT	CONTAIN
T			
W	V	LTS	CONTAIN
X			
Y	V	BA & FIRE KIT	CONTAIN
Z			
E		PUBLIC SAFETY HAZARD	

* SEE LEGEND OVER

LEGEND	
DRY AGENT	Do not use water
ALCOHOL RESISTANT FOAM *2 OR *3	When * appears in front of 2 or 3 in Hazchem code use alcohol resistant foam if available
V	Substances can be violently or even explosively reactive, including combustion
LTS	Liquid-Tight Chemical Protective Suit with BA. Full FIRE KIT to also be worn for protection when: Liquid Oxygen or Liquefied Toxic Gas (Division 2.3) or Toxic Gas with sub-risk 2.1 or 5.1 or Class or sub-risk 3 or Division 5.1 PGI with sub-risk 6.1 or 8 transported at temperature >100°C are involved
DILUTE	May be washed to drains with large quantities of water, consider EPA or Water Authority
CONTAIN	Prevent, by any means available, spillage from entering drains or water courses
E	People to be warned to stay indoors with all doors and windows closed. Evacuation may need to be considered. Joint Incident Control decision



7. HANDLING AND STORAGE

- Precautions for Safe Handling :**
- Eye wash to be available in the workplace.
 - Wear PPE as per this SDS
 - Compliant eyewash to be provided for external work.
 - Observe good personal hygiene practices.
 - Wash hands thoroughly after handling.
 - Avoid contact with skin and eyes.
 - Limit the stock at work place (in accordance with **AS1940: The storage and handling of flammable and combustible liquids**)
 - Use only in well ventilated areas.
 - Wear respiratory protection if oil mists present.
 - Report incidents.
 - No smoking, eating, drinking in the work area.
 - Remove contaminated clothing before entering eating areas.
- Conditions for Safe Storage :**
- Store away from food, drink and animal feedstuffs.
 - Store away from oxidising agents.
 - Provide ventilation.
 - Separate or segregate from incompatibles (in accordance with regulatory requirements).
 - Avoid direct sunlight.
 - Keep protected from weather.
 - Provide spill kit.
- Container Type :**
- Store in original packaging as approved by manufacturer or regulatory direction.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CONSTITUENT DATA

Components	CAS-No.	Type	Value
Oil Mist		TWA	5mg/m ³

ENGINEERING CONTROLS

- Provide local exhaust ventilation when exposure standards might be exceeded. Oil mists are unlikely due to high viscosity of the product.

PERSONAL PROTECTION

- Eye Protection :** Not required for normal use. Where contact may occur, wear chemical splash goggles or face shield in accordance with **AS/NZS1337, Eye protection for industrial applications.**
- Gloves :** Wear chemical protective gloves (eg PVC or nitrile) in accordance with **AS/NZS 2161.1 - Occupational protective gloves, selection, use and maintenance** where contact may occur.
- Clothing :** Wear body protective clothing and industrial footwear in accordance with **AS2919 - Industrial clothing.**
- Respiration :** If oil mists are present when ventilation is inadequate, wear an approved respirator with particulate/mist filter in accordance with **AS/NZS1715 - Selection, use and maintenance of respiratory protective devices**



Available



Side shields



PVC/nitrile



Industrial



Non slip



Particulate



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Amber or Brown Grease
Odour	:	Mild
pH	:	Not provided
Vapour Pressure (kpa)	:	Not provided
Vapour Density	:	Not provided
Boiling Point	:	Not provided
Freezing / Melting Point	:	Not provided
Solubility in Water	:	Not soluble
Solubility in Solvents	:	Soluble in petroleum solvents
Specific Gravity or Density	:	

INFORMATION FOR FLAMMABLE MATERIALS

Flash Point	:	>250°C
Upper Explosive Limit	:	NOT PROVIDED
Lower Explosive Limit	:	NOT PROVIDED
Ignition Temperature	:	Not provided

ADDITIONAL INFORMATION

Specific Heat Value	:	Not provided
Particle Size	:	Not provided
VOC Content	:	Not provided
Evaporation Rate	:	Not provided
Kinematic Viscosity @ 40°C	:	Not provided
Kinematic Viscosity@ 100°C	:	Not provided
Octanol / Water Partition Coefficient	:	Not provided
Saturation Vapour Concentration	:	Not provided
Decomposition Temperature	:	Not provided
Electrostatic Stability	:	Not provided

10. STABILITY AND REACTIVITY

Chemical Stability	:	Product is stable under normal conditions of use, storage and temperature.
Conditions to Avoid	:	Avoid excessive heat, static charges, sources of ignition.
Incompatible Materials	:	Incompatible with strong oxidising agents.
Hazardous Decomposition Products	:	Oxides of carbon, nitrogen and sulphur, dense black smoke, toxic decomposition gases, and airborne unidentified organic and inorganic solid and liquid particulates - see Section 5.
Hazardous Reactions	:	When heated above 250°C, vapours may form flammable mixture with air

11. TOXICOLOGICAL INFORMATION

ACUTE HEALTH EFFECTS (IMMEDIATE OR WITHIN 14 DAYS - SHORT TERM)

Swallowed (Oral)	:	If ingested may cause gastric irritation.
Eye	:	Mild Eye irritant.
Skin (Dermal)	:	Mildly irritating to skin on prolonged exposure. Repeated or prolonged skin contact may result in defatting, and dermatitis.
Inhalation	:	Strong concentrations of mist or spray may be irritating to the respiratory tract and for mucous membranes with the risk of headaches, dizziness and nausea.

CHRONIC (MEDIUM OR LONG TERM)

- Long term exposure may result in skin sensitisation in susceptible individuals.

MIXTURE VERSUS INGREDIENT

- Acute toxicity - oral, ATE oral (mg/kg) 3,900

SUMMARY OF TOXICITY DATA

Component	CAS-No.	Data
Not available		

CARCINOGENICITY

- None known.

FOR OILS AND GREASES

USED OILS AND GREASES

- Products resulting from the operation of the vehicle/ machinery may contain contaminants. Used oil and grease may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used oil and grease must therefore be avoided and a high standard of personal hygiene maintained.
- Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
- At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of low volatility. May be harmful by inhalation if exposure to mists or fumes resulting from thermal decomposition products occur.

12. ECOLOGICAL INFORMATION

Ecotoxicity	:	Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.
Persistence / Degradability	:	Will persist. Not readily bio degradable.
Mobility	:	Non-volatile, Floats on water - poorly absorbed by soil.
Bio-accumulative Potential	:	No data
Environmental Fate (Exposure)	:	Do not allow waste product to reach waterways, drains and sewers

13. DISPOSAL CONSIDERATIONS

Disposal Methods	:	Do not dispose to drains or waterways.
Special Precautions for Landfill or Incineration	:	Dispose using a licensed contractor. Suitable for incineration where applicable regulations permit..

14. TRANSPORT INFORMATION

Special Precautions	:	Not regulated under Australian or International Dangerous Goods Codes, but Class 5 goods require segregation from combustible liquids in placard loads.
UN Number	:	Not allocated
UN Proper Shipping Name	:	Not allocated
Dangerous Goods Class and Subsidiary Risk	:	Not dangerous goods, C2 Combustible Liquid
Packing Group	:	Not allocated
Hazchem Code	:	3Y

15. REGULATORY INFORMATION (AUSTRALIA)

- Workplace Exposure Standards for Atmospheric Contaminants [Safe Work Australia, April 2013]
- Australian Code for Transport of Dangerous Goods by Road and Rail
- AS1940: The storage and handling of flammable and combustible liquids
- State Work Health and Safety/Occupational Health and Safety Regulations

16. OTHER INFORMATION

- References :** For detailed advice on personal protective equipment, refer to the following Australian Standards:
- HB9 (Handbook 9) Manual of industrial personal protection
 - AS/NZS 1337: Eye protectors for industrial applications
 - AS/NZS 1715: Selection, use and maintenance of respiratory devices
 - AS/NZS 1716: Respiratory protective devices

CONTACT POINT

For information concerning details on this Safety Data Sheet, **Phoenix Lubricants Pty Ltd, 2 Paul Court, Dandenong Vic, (03) 9791 7661**

All reasonable care has been taken to ensure that the information and advice contained herein is accurate at the time of printing. However, Phoenix Lubricants Pty Ltd accepts no tortious or contractual liability for any loss or damages suffered as a consequence of reliance on the information and advice contained herein.

Note:

This SDS is derived from International and Australian data and is formatted in accordance with the Safe Work Australia Code of Practice. Modifications are not made to technical data except where terminology is unclear or additional information is required to satisfy Australian requirements.

SOURCE FOR DATA

- MSDS Issue Date :** 02/03/2013
- SDS Revision 2.2 Date :** 12/08/2019
- Manufacturer / Supplier :** Phoenix Lubricants Pty Ltd
-