Technical Data

TECHNICIAN SERIES PX TRANSMATIC VI

Product Description

PX Transmatic VI is low viscosity premium synthetic automatic transmission fluid that has been specially formulated to meet the latest GM/ Holden transmission requirements. The synthetic fluid based combined with superior additive technology, gives a product that provides exceptional low viscosity with improved low temperature performance, shear and friction stability.

Applications/ Benefits

PX Transmatic VI is premium automatic transmission fluid suitable for late model and imported vehicles such as those from Holden, Opal and Chevrolet. It can also be used for power steering applications except where specialized fluids are called for.

- Provides improved shift feel, friction durability and oxidative stability
- Excellent low temperature fluidity
- Provides better fuel economy
- Superior anti-wear protection
- Suits most 2006 and later GM manufactured transmissions

Typical Characteristics

Test Description	Result
Colour	Red
Specific Gravity @ 15 0 C	0.846
Flash Point, Deg. C	198
Pour Point, Deg. C	-45
Kinematics Viscosity @ 40C (cSt)	27.13
Kinematics Viscosity @ 100 0 C (cSt)	5.75
Viscosity Index	158

Specifications

- DEXRON VI[©]
- Aisin Warner AW-1
- HONDA DW-1
- GM PN 88863400, 88863401
- NISSAN/INFINITY: MATIC S



PHOENIX LUBRICANTS 2 Paul Court Dandenong Victoria 3175 Tel. +61 3 9791 7661

www.phoenixlubricants.com.au Email: info@phoenixlubricants.com.au • VW: G 055 005, 055 0540

• CHRYSLER: 68171866AA, 68171869AA

HYUNDAI: SP-IV, NWS-9638 T-5

MAZDA: FZ

• MITSUBISHI:SP-IV, ATF J3

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.





